

MyService

MIFARE® Technology Activation System



Security, Flexibility and Ease of Use

Payment Box to Manage Up to 6 Different Programs or Services

Thanks to the EuroKey Next cashless system and the RM5 HD coin validator, MyService ensures security and flexibility. Suitable for the payment automatism of several timed services (such as service areas, self-service, laundrettes, sport and tourist facilities, public services and timed lighting) and for managing sales and identification applications. Also available with WorldKey cashless system for advanced accounting management.

Features

- ✓ Sturdy anti-vandal and waterproof cabinet, weather agents protection
- ✓ High safety lock
- ✓ Automatic service activation through cards, keys, tags or coins (in the coin mechanism version) or through the selection buttons
- ✓ Alphanumeric display with 16 characters in 2 lines
- ✓ Rear cable exit
- ✓ Internal on/off switch
- ✓ Power supply: 230 V or 24 V

Functionality

- ✓ Up to 6 timed services management and automation
- ✓ 3 safety codes management (administrator, renter, machine)
- ✓ Machine No. modifiable by the user
- ✓ Single cash sales or multiple cash sales*
- ✓ Maximum value management
- ✓ Differentiated cards/keys/tags management
- ✓ Black list/white list/log file management*
- ✓ Time slots management
- ✓ Bonus management
- ✓ Advanced promotional campaigns management
- ✓ Accounting data management
- ✓ On-field firmware updates
- ✓ Remote data management*
- (*) only with WorldKey cashless system

Tools

UNICO configuration program

To collect and manage audit/log data (pursuant to the EVA-DTS standard or Windows Excel), program operating parameters and manage all functions of cards/keys/tags

Card management software (code RFT-CARD-SW)

Audit and log management software (code RFT-AUDIT-SW)

Portable universal programmer

To program MyService directly on field or to download audit data via infrared

Programming key and Clone programming key

Audit key



Optional Accessories

- ✓ Customisable RFID keys/cards/tags/stickers by quantity
- ✓ Micro USB cable



Technical Specifications

Dimensions (LxHxD)	208 x 410 x 96.5 mm
Weight	8.5 Kg
Mounting	Wall-mount
Input voltage	Main versions: 230 Vac ± 10% Low voltage: 12 ÷ 24 Vdc ± 10%
Power consumption	40 W
Outputs	Relay, current-carrying capacity 4A at 230 Vdc

Technical Specifications – keys/cards/tags

Technology used	Inductive transmission, data and energy ISO 14443 – MIFARE® encrypted		
Transmission frequency	13,56 MHz		
Coin Capacity	0.50 €	1 €	2 €
Coin capacity	400	500	350